Standard EN 420: 2003 : Marking & Information

Marking of the glove

- Each glove should be marked with:
- Name of manufacturer
- > Glove and size designation
- CE mark
- Appropriate pictograms accompanied by the relevant performance levels and the reference of the EN standard.
- The marking should be legible throughout the life of the glove. Where marking of the glove is not possible in view of the characteristics of the glove, it should be mentioned on the first packaging enclosure.

Marking of the packaging immediately containing the gloves:

- Name and address of the manufacturer or representative
- > Glove and size designation
- CE mark
- Usage info
- simple design: for minimal risks only
- intermediate design or complex design: relevant pictograms
- when protection is limited to part of the hand, this shall be mentioned (e.g. Palm Protection style only)
- Reference to where information can be obtained.

Instructions for Use (to be supplied when the glove is placed on the market):

- Name and address of the manufacturer or representative
- Glove designation
- Size range available
- CE mark
- Care & storage instruction
- > Instructions and limitations of use
- A list of substances used in the glove which are known to cause allergies
- A list of all substances in the glove shall be made available upon request
- Name and address of Notified Body that certified the product.

Sizing of gloves

Glove Size	Fits hand Size	Hand Circumference/length (mm)	Minimum length of the glove (mm)
6 / XS	6	160/152	220
7/S	7	178/171	230

Website: http://www.anysafe-glove.com/

ANYSAFE INDUSTRIAL - Your Protection Expert

8 / M	8	203/182	240
9 / L	9	229/192	250
10 / XL	10	254/204	260
11 / XXL	11	279/215	270

Glove dexterity

Performance level	Smallest diameter of pin that can be picked up with gloved hand : 3 times / 30 seconds (mm)
1	11.0
2	9.5
3	8.0
4	6.5
5	5.0

Website: http://www.anysafe-glove.com/